



MATERIAL SAFETY DATA SHEET

Axson North America, Inc.
1611 Hults Drive Eaton Rapids, MI 48827
(517)663-8191 24hrs (800)424-9300

1/17/2008

1- COMMERCIAL NAME : H 9930 NA Epoxy Hardener

Do not handle this material until the manufacturer's safety precautions have been read and understood! Regulations require that all employees be educated & trained on the Material Safety Data Sheets for all products with which they come in contact.

2- COMPOSITION/INFORMATION ON INGREDIENTS :

CHEMICAL NAME	C.A.S No.	QTY%
1. Mercaptan terminated polymer	trade secret	85-95
2. Tertiary amine	trade secret	1-5
3. N/A	N/A	N/A

3- HAZARDS IDENTIFICATION :

- Irritant to skin and eyes (may cause possible corneal injury).
- Harmful if swallowed or absorbed through the skin.
- May cause skin sensitization, allergic reaction, and/or dermatitis.
- Vapors/mists may cause upper respiratory tract irritation. Repeated exposure can cause damage to mucous membranes. Can enter the lungs and cause damage.
- May cause gastrointestinal irritation if swallowed; corrosive to mouth, throat, and stomach.

4- FIRST AID MEASURES :

- **Where a serious accident occurs, seek medical advice immediately.**
- **Change any soiled clothing immediately.**
- **In case of eye contact** : open eyelids as far as possible and flush with large quantities of water for at least fifteen minutes. Seek immediate medical attention.
- **In case of skin contact** : physically remove the product and wash skin thoroughly with soap and water. Seek immediate medical attention if irritation develops.
- **In case of swallowing** : give 1-2 glasses of milk or water to conscious person. **DO NOT** induce vomiting. If vomiting does occur, give fluids again. Contact Poison Control and seek immediate medical attention.
- **In case of inhalation** : remove the patient from the contaminated area, give oxygen if necessary. Consult physician if after-effects occur.

5- FIRE-FIGHTING MEASURES :

5-1 Fire-extinguisher types :

- Use : chemical foam, CO₂, powder. Where the fire is of major proportions, water spray may also be used.

5-2 Specific fire and explosion risks :

Incomplete combustion or pyrolysis mainly produces oxides of carbon monoxide, carbon dioxide, hydrogen sulfide, or oxides of sulfur may be released upon combustion. Prevent exposure to combustion products.

5-3 specific protective measures during firefighting :

Firefighting personnel should be equipped with insulated, autonomous respiratory protection equipment.

COMMERCIAL NAME : H 9930 NA Epoxy Hardener**6- ACCIDENTAL RELEASE MEASURES :****6-1 Individual protection :**

Wearing of suitable protective clothing and protective equipment for face/eyes; wear suitable respiratory equipment if ventilation is insufficient.

6-2 Environmental protection : Please see § 12

6-3 Decontamination procedures :

- Contain spilt material in order to avoid its transfer to sewers or rivers and streams.
- Physically remove the material.
- Cover material with sand, earth, or any other similar absorbent material in order to soak product up. The resulting mix may then be shoveled into cans and removed for disposal (see §13).

7- HANDLING AND STORAGE :**7-1 Handling :**

- Inform personnel of risks associated with the product, the precautions to be taken and procedures to follow where an accident occurs.
- Observe personal hygiene rules to avoid contact with eyes and skin.
- Avoid inhaling vapors produced by the material, **especially when heated and/or sprayed.**
- Install showers and eye baths ("fountain" type).
- Ensure sufficient ventilation, including appropriate local air extraction, in order to comply with workplace exposure limits.
- Wash hands thoroughly at beginning of every work break and at the end of the working day.
- Work stations and the general working area must be kept perfectly clean.
- Avoid exposure to the product of persons having suffered from eczema or still suffering from any skin condition, wound, cut or irritation.

7-2 Storage :

- Keep the material hermetically sealed in its original packaging, protected from humidity and at a temperature between 59 and 77°F / 15 and 25°C in a well-ventilated storage facility.
- Ensure that the floor of the storage area is impermeable and concave in profile in order to provide effective containment.
- Keep the product away from food.
- Reproduce labeling on all new packs where original packaging is divided.

8- EXPOSURE CONTROLS/PERSONAL PROTECTION :**8-1 Exposure controls :**

Always maintain workplace airborne contaminants to the lowest possible levels.

8-2 Personal protection :

- respiratory protection : NO, when vapors are below PEL recommendations. Recommended if product is heated and/or sprayed.
- eye protection : YES, safety glasses with side shields, or chemical-goggles with faceshield
- skin protection : YES, protective gloves, such as nitrile, butyl, PVC, rubber, or neoprene

Do not mix work clothing and normal clothing. Wash hands thoroughly at beginning of every work break and at the end of the working day.

COMMERCIAL NAME : H 9930 NA Epoxy Hardener**9- PHYSICAL AND CHEMICAL PROPERTIES :**

Physical state : paste

Color : light yellow

Odor : sulfur-like

pH : not established

Flash point : > 495°F / 257°C

Decomposition temperature : > 392°F / 200°C

Specific gravity : 1.13

Solubility : slight

10- STABILITY AND REACTIVITY :**10-1 Dangerous decomposition by-products :**

- These are non-existent if storage and handling rules are followed (please see also § 5-2).
- Carbon monoxide and/or carbon dioxide during thermal decomposition. Irritating and toxic fumes at elevated temperatures.

10-2 Hazardous reactions with :

- Do not allow uncontrolled reactions with epoxy resins, strong acids, or strong oxidizing agents.

11- TOXICOLOGICAL INFORMATION :

Effects on eyes : may cause severe ocular irritation. Vapors may also cause eye irritation and pain.

Effects on skin : a single short exposure may cause skin sensitization/burns; caustic effect on skin and mucous membranes. **LD50 (rabbit): >10.2 g/kg**

Inhalation : excessive exposure may cause irritation to the upper respiratory tract and mucous membranes. May lead to sensitization or respiratory system or asthma in predisposed individuals.

Ingestion : may cause gastrointestinal irritation or ulceration. May cause irritation of mouth, throat, and stomach. **LD50 (rat): >2.6 g/kg**

12- ECOLOGICAL INFORMATION :

Ecotoxicity : no data

Environmental fate : no data

13- DISPOSAL CONSIDERATIONS :

All disposal methods must be in compliance with all Federal, State/Provincial and local regulations. Regulations may vary in different locations. Waste characteristics and compliance with applicable laws are the responsibility solely of the waste generator. Empty containers may not be disposed of unless any remaining material adhering to the internal walls has been removed (see § 6.3).

COMMERCIAL NAME : H 9930 NA Epoxy Hardener**14- TRANSPORT INFORMATION :****DOT Regulations/Information :****Proper Shipping Name :** Environmentally Hazardous Substance, Liquid, N.O.S.
(Mercaptan terminated polymer)**UN/NA No. :** 3082**Packing Group :** III**Hazard Class :** 9**Internal label :** H007020A**15- REGULATORY INFORMATION :****US Federal Regulation :****Toxic Substances Control Act (TSCA) :**

All components are included in the EPA Toxic Substances Control Act Chemical Substance Inventory.

OSHA Hazard Communication Standard Hazard Classes :

Hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

OSHA PEL/TWA : none established**ACGIH TLV/TWA :** none established**EPA SARA Title III Section 313 Toxic Chemicals :** none**16- OTHER INFORMATION :****HMIS Ratings:****Health. Flammability. Reactivity**

2.1.0.

Ratings Key: 4 = Highest hazard, 0 = Lowest hazard, * = Chronic Health Hazard**REVEALING MODIFICATION : A5.PDF**

Revised : 1/17/2008 Supersedes sheet : 8/10/2007 This sheet provides a complement to the product use instructions but does not replace them. The information it contains is based on our current knowledge of the product concerned at the date of drafting. That information is given in good faith and does not in any circumstances remove from the user his duty to be aware of and to follow all legal regulations and statutes covering his activities. The user takes sole responsibility for application of safety measures covering the use of the product he is aware of. We also draw the user's attention to the risks attached to any use of the product for applications for which it was not designed.
03/2006