



MATERIAL SAFETY DATA SHEET

Axson North America, Inc.
1611 Hults Drive Eaton Rapids, MI 48827
(517)663-8191 24hrs (800)424-9300

9/11/2007

1- COMMERCIAL NAME : Tile-Stone 100 Epoxy Hardener

Do not handle this material until the manufacturer's safety precautions have been read and understood! Regulations require that all employees be educated & trained on the Material Safety Data Sheets for all products with which they come in contact.

2- COMPOSITION/INFORMATION ON INGREDIENTS :

CHEMICAL NAME	C.A.S No.	QTY%
1. Aminoethylpiperazine	140-31-8	1-10
2. Tetraethylenepentamine (reacted)	112-57-2	1-10
3. Polymer of TETA & TOFA	68082-29-1	30-40
4. N/A	N/A	N/A

3- HAZARDS IDENTIFICATION :

- Corrosive to skin and eyes (may cause severe eye damage or blindness). Harmful if swallowed or absorbed through the skin. Severe skin irritant.
- May cause skin sensitization, allergic reaction, dermatitis, and burns.
- Vapors/mists may cause upper respiratory tract irritation. Repeated inhalation may cause lung damage.
- May cause gastrointestinal irritation and possibly burns if swallowed; corrosive to mouth, throat, and stomach.

4- FIRST AID MEASURES :

- **Where a serious accident occurs, seek medical advice immediately.**
- **Change any soiled clothing immediately.**
- **In case of eye contact** : open eyelids as far as possible and flush with large quantities of water for at least twenty minutes. Seek immediate medical attention.
- **In case of skin contact** : physically remove the product and wash skin thoroughly with soap and water. Seek immediate medical attention.
- **In case of swallowing** : give 3-4 glasses of milk or water to conscious person. **DO NOT** induce vomiting. If vomiting does occur, give fluids again. Contact Poison Control and seek immediate medical attention.
- **In case of inhalation** : remove the patient from the contaminated area, give oxygen if necessary. Consult physician if after-effects occur.

5- FIRE-FIGHTING MEASURES :

5-1 Fire-extinguisher types :

- Use : chemical foam, CO₂, powder. Where the fire is of major proportions, water spray may also be used.

5-2 Specific fire and explosion risks :

Incomplete combustion or pyrolysis mainly produces oxides of carbon monoxide, nitrogen oxide, and ammonia gas may be released upon combustion. Prevent exposure to combustion products.

5-3 specific protective measures during firefighting :

Firefighting personnel should be equipped with insulated, autonomous respiratory protection equipment.

COMMERCIAL NAME : Tile-Stone 100 Epoxy Hardener**6- ACCIDENTAL RELEASE MEASURES :****6-1 Individual protection :**

Wearing of suitable protective clothing and protective equipment for face/eyes; wear suitable respiratory equipment if ventilation is insufficient.

6-2 Environmental protection : Please see § 12

6-3 Decontamination procedures :

- Contain spilt material in order to avoid its transfer to sewers or rivers and streams.
- Physically remove the material.
- Cover material with sand, earth, or any other similar absorbent material in order to soak product up. The resulting mix may then be shoveled into cans and removed for disposal (see §13).

7- HANDLING AND STORAGE :**7-1 Handling :**

- Inform personnel of risks associated with the product, the precautions to be taken and procedures to follow where an accident occurs.
- Observe personal hygiene rules to avoid contact with eyes and skin.
- Avoid inhaling vapors produced by the material, **especially when heated and/or sprayed.**
- Install showers and eye baths ("fountain" type).
- Ensure sufficient ventilation, including appropriate local air extraction, in order to comply with workplace exposure limits. **Avoid breathing dusts generated during the machining of cured material.**
- Wash hands thoroughly at beginning of every work break and at the end of the working day.
- Work stations and the general working area must be kept perfectly clean.
- Avoid exposure to the product of persons having suffered from eczema or still suffering from any skin condition, wound, cut or irritation.

7-2 Storage :

- Keep the material hermetically sealed in its original packaging, protected from humidity and at a temperature between 59 and 77°F / 15 and 25°C in a well-ventilated storage facility.
- Ensure that the floor of the storage area is impermeable and concave in profile in order to provide effective containment. Do not store in reactive metal containers.
- Keep the product away from food.
- Reproduce labeling on all new packs where original packaging is divided.

8- EXPOSURE CONTROLS/PERSONAL PROTECTION :**8-1 Exposure controls :**

Always maintain workplace airborne contaminants to the lowest possible levels.

8-2 Personal protection :

- respiratory protection : NO, when vapors are below PEL recommendations. Recommended if product is heated and/or sprayed. Wear dust mask during machining of cured material.
- eye protection : YES, safety glasses with side shields, or chemical-goggles and full face-shield.
- skin protection : YES, protective gloves, such as nitrile, butyl, PVC, rubber, or neoprene

Do not mix work clothing and normal clothing. Wash hands thoroughly at beginning of every work break and at the end of the working day.

COMMERCIAL NAME : Tile-Stone 100 Epoxy Hardener**9- PHYSICAL AND CHEMICAL PROPERTIES :**

Physical state : thick paste

Color : amber

Odor : characteristic

pH : not established

Flash point : > 239°F / 115°C

Decomposition temperature : > 392°F / 200°C

Specific gravity : 1.51

Solubility : slight

10- STABILITY AND REACTIVITY :**10-1 Dangerous decomposition by-products :**

- These are non-existent if storage and handling rules are followed (please see also § 5-2).
- Carbon monoxide, carbon dioxide, ammonia when heated, nitric acid, and volatile amines during thermal decomposition. Irritating and toxic fumes at elevated temperatures.

10-2 Hazardous reactions with :

- Avoid contact with oxidizing materials such as: peroxides, chlorates, and permanganates. Do not allow uncontrolled reactions with epoxy resins, acids, anhydrides, or chloride acid compounds - can create corrosive gas/vapors. Do not use sodium nitrate or other nitrosating agents in formulations containing this product.

11- TOXICOLOGICAL INFORMATION :

Effects on eyes : corrosive; may cause severe ocular irritation. Vapors may also cause eye irritation and pain.

Effects on skin : corrosive; a single short exposure may cause skin sensitization/burns; caustic effect on skin and mucous membranes. **LD50 (rabbit): 880mg/kg (AEP); LD50 (rabbit): 8550mg/kg (TETA/TOFA);**

LD50 (rabbit): 2000mg/kg (Reacted TETA)

Inhalation : excessive exposure may cause irritation and or burns to the upper respiratory tract. May lead to sensitization or respiratory system or asthma in predisposed individuals.

Ingestion : may cause gastrointestinal irritation or ulceration. May cause burns of mouth, throat, and stomach. Swallowing will lead to a strong caustic effect on mouth and throat, and to the danger of perforation of the esophagus and/or stomach. **LD50 (rabbit): no data (AEP); LD50 (rat): 4750mg/kg (TETA/TOFA);**
LD50 (rat): 2000mg/kg (Reacted TETA)

12- ECOLOGICAL INFORMATION :

Ecotoxicity : no data

Environmental fate : no data

Additional information : waste from this product may present long term environmental hazards, thus landfill disposal must be considered less acceptable than incineration.

13- DISPOSAL CONSIDERATIONS :

All disposal methods must be in compliance with all Federal, State/Provincial and local regulations. Regulations may vary in different locations. Waste characteristics and compliance with applicable laws are the responsibility solely of the waste generator. Empty containers may not be disposed of unless any remaining material adhering to the internal walls has been removed (see § 6.3). This product, if disposed, may be considered a corrosive waste (D002) under current RCRA regulations.

COMMERCIAL NAME : Tile-Stone 100 Epoxy Hardener**14- TRANSPORT INFORMATION :****DOT Regulations/Information :****Proper Shipping Name :** Amines, Liquid, Corrosive, N.O.S. (Aminoethylpiperazine)**Hazard Class :** 8 (corrosive)**UN/NA Number :** UN2735**Packaging Group :** III**Internal label :** H2265200**15- REGULATORY INFORMATION :****US Federal Regulation :****Toxic Substances Control Act (TSCA) :**

All components are included in the EPA Toxic Substances Control Act Chemical Substance Inventory.

OSHA Hazard Communication Standard Hazard Classes :

Hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

Corrosive; Sensitizer, Irritant, Toxic by skin absorption.

EPA SARA Title III Section 312 Hazard Class : Immediate Health Hazard; Delayed Health Hazard**OSHA PEL/TWA & ACGIH TLV/TWA :** TWA (TETA): 1ppm - 6mg/m³**EPA SARA Title III Section 313 Toxic Chemicals :** none**This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 or greater.****16- OTHER INFORMATION :****HMIS Ratings:****Health. Flammability. Reactivity****3.1.1.****Ratings Key: 4 = Highest hazard, 0 = Lowest hazard, * = Chronic Health Hazard****REVEALING MODIFICATION : A3.4.PDF**

Revised : 9/11/2007 Supersedes sheet : N/A This sheet provides a complement to the product use instructions but does not replace them. The information it contains is based on our current knowledge of the product concerned at the date of drafting. That information is given in good faith and does not in any circumstances remove from the user his duty to be aware of and to follow all legal regulations and statutes covering his activities. The user takes sole responsibility for application of safety measures covering the use of the product he is aware of. We also draw the user's attention to the risks attached to any use of the product for applications for which it was not designed. 03/2006